

## SOLO Standard Configuration files (Compliant with the Minimum Receiver Requirements)

Combination	1	2	3	4	5	6
Frequency range	Tunable LF/MF (from 148,5kHz to 1710kHz)		Tunable HF (from 2,3Mhz to 27MHz)			
Robustness mode	A	A	B	B	C	D
Channel bandwidth	9kHz	9kHz	10kHz	10kHz	10kHz	10kHz
MSC mode	64-QAM	64-QAM	64-QAM	64-QAM	16-QAM	64-QAM
Protection level	EEP-3	EEP-2	EEP-3	EEP-1	EEP-1	EEP-0
Interleaver depth	Short	Short	Long	Long	Long	Long
SDC mode	16-QAM	16-QAM	16-QAM	16-QAM	4-QAM	16-QAM
Audio mode	Parametric Stereo	Parametric Stereo	Parametric Stereo	Parametric Stereo	Mono	Mono
Audio bit rate (bps)	30 700	27 700	27 250	20 800	11 300	8980
SBR	Yes	Yes	Yes	Yes	No	No
Text messages	Yes	Yes	Yes	Yes	Yes	Yes

**Other files can be sent on request for testing Simulcast (with or without Shaping), data insertion (MOT, IP Tunnelling...), the Automatic Frequency Switching (AFS), the AMSS (AM Simple Signaling System) or other DRM applications.**